




AccuPulse® HR Series

| MODELS | | EYFLA7A | EYFLA8A / EYFLA8C / EYFLA8P | EYFLA9C / EYFLA9P |
|--|----------|--|--|--|
| | |  |  |  |
| Voltage | | 10.8V | 10.8V | 10.8V |
| Series | | AccuPulse - HR Series | | |
| Drive | | A = 1/4" Hex Quick Change | A = 1/4" Hex Quick Change C = 3/8" Sq. C-Ring w/ through Hole P = 3/8" Sq. Pin Detent | C = 1/2" Sq. C-Ring w/ through Hole P = 1/2" Sq. Pin Detent |
| Torque Range | Nm | 3-22Nm | 6-30Nm | 20-60Nm |
| | ft. lbs. | 2.2-16.2 ft. lbs. | 4.4-22 ft. lbs. | 14.75-44.25 ft. lbs. |
| | in. lbs. | 26.55-194.72 in. lbs. | 53.1-265.52 in. lbs. | 177.01-531.04 in. lbs. |
| Max Torque* [F mode, tightening 3 sec.] | | 35Nm M10 Bolt | 80m M14 Bolt | 120Nm M14 Bolt |
| Flush Detection Modes | | L1 - L7 | L1 - L7 | L1 - L7 |
| No Load Speed [Torque Setting: RPM] | | 1: 0 - 950 2: 0 - 1250 3: 0 - 1450 4 - 8: 0 - 1550 9 - 40 & F: 0 - 2300 | 1: 0 - 1300 2: 0 - 1450 3: 0 - 1550 4 - 40 & F: 0 - 2300 | 1-40 & F: 0-2300 |
| PPM (Pulses Per Min) | | 1: 0 - 1900 2: 0 - 2500 3: 0 - 2800 4-8: 0 - 3000 9-30 & F: 0 - 4000 | 1: 0-2500 2: 0-2800 3: 0-3000 4-30 & F: 0-3600 | 1-40 & F: 0-2800 |
| Weight | | 2.53 lbs. (incl. 2.0Ah [EYFB32B]) 2.86 lbs. (incl. 3.0Ah [EYFB30B]) | 2.53 lbs. (incl. 2.0Ah [EYFB32B]) 2.86 lbs. (incl. 3.0Ah [EYFB30B]) | 2.53 lbs. (incl. 2.0Ah [EYFB32B]) 2.86 lbs. (incl. 3.0Ah [EYFB30B]) |
| Size (L x W x H) | | 6-1/32 x 9-51/64 x 2-61/64 H=9-51/64[EYFB30B] 9-3/32 [EYFB32B] | 8A: 6-1/32 x 9-51/64 x 2-61/64 8C: 6-3/8 x 9-51/64 x 2-61/64 H=9-51/64[EYFB30B] 9-3/32 [EYFB32B] | 6-49/64 x 9-27/64 x 2-61/64 H=9-27/64[EYFB42B], 9-9/64 [EYFB41B] |
| Wireless Communication with Assembly Qualifier: | | — | — | — |
| LED Work Light: [ON/OFF Switch] | | ✓ | ✓ | ✓ |
| OK/NOK Light: [Green: OK / Red: NOK] | | ✓ | ✓ | ✓ |
| Rehit Prevention: (Possible to set per 0.1 sec. between 0-3 sec.) | | ✓ | ✓ | ✓ |
| Battery Indication Lamp: [3 stage] | | ✓ | ✓ | ✓ |
| Low Power Disable | | ✓ | ✓ | ✓ |
| Prevent / Detect Cross Threads & Rehits | | ✓ | ✓ | ✓ |
| Maintenance Interval Alarm | | ✓ | ✓ | ✓ |
| Variable Speed On / Off Switch | | ✓ | ✓ | ✓ |
| Variable Speed On / Off Switch | | ✓ | ✓ | ✓ |
| Buzzer: On / Off | | ✓ | ✓ | ✓ |
| Flush Point Detection Delay (Possible to set between 0-3 sec.. 0.1 sec. per stage) | | ✓ | ✓ | ✓ |
| Socket Extension Mode (h1:150mm socket, h2: for 250mm socket) | | ✓ | ✓ | ✓ |
| Work Capacity / Fastening Speed* | | <M6: 10 N·m, Stage: 22> [EYFB30B] 1200 pcs/pack 0.7 sec/1pcs [EYFB32B] 800 pcs/pack 0.7 sec/1pcs | <M8: 23 N·m, Stage: 22> [EYFB30B] 800pcs/pack 0.8sec/1pcs [EYFB32B] 540 pcs/pack 0.8 sec/1pcs | <M10: 43 N·m, Stage: 23> [EYFB30B] 400 pcs/pack, 0.8 sec/1pcs [EYFB32B] 260 pcs/pack, 0.8 sec/1pcs |
| Charging Time* | | [Battery pack EYFB30B, Charger EY0L82B] Usable charge: 35 min., Full charge: 45 min [Battery Pack EYFB32B, Charger EY0L82B] Usable Charge: 35 min., Full Charge: 40 min | | |

Note: *Approximately

